


Product Data Sheet

DIAION™ CRB05

DIAION™ CRB05 is a glucamine type chelating resin. It has a high selectivity for borate ion and higher capacity than DIAION™ CRB03. It is recommended for borate separation process from various solutions, including brines, sea water and waste water.

Product

Grade Name	DIAION™ CRB05	
Type	Chelating Resin	
Matrix	Styrene-DVB, Highly Porous	
Chemical Structure		
Functional Group	N-Methyl Glucamine	
Ionic Form	Free Base	

Specification

Whole Bead Count	-	95 min.
Total Exchange Capacity	meq/mL	0.95 min.
Water Content	%	43 - 53
Particle Size Distribution on 850 μm	%	10 max.
Particle Size Distribution thr. 300 μm	%	1 max.
Effective Size	mm	0.35 min.
Uniformity Coefficient	-	1.6 max.

Typical Properties

Shipping Density	g/L	750
Mean Particle Size	μm	550
Boron Adsorption Capacity	mg/mL-R	25
Particle Density	g/mL	1.13
Total Swelling (FB to Cl ⁻)	%	11

DIAION™ CRB05**Recommended Operating Conditions**

Maximum Operating Temperature	°C	100
Effective pH Range		6 - 10
Minimum Bed Depth	mm	800
Service Flow Rate	m/h	5 - 20
Eluate		HCl
Eluate Concentration	%	HCl 2 - 4
Eluate Level	g/L	50 - 100
Eluate Flow Rate	m/h	1 - 3
Regenerant		NaOH
Regenerant Concentration	%	NaOH 2 - 4
Regenerant Level	g/L	20 - 40
Regenerant Flow Rate	m/h	1 - 3
Total Rinse Requirement	BV	10 - 20



Hydraulic Characteristics

The approximate pressure drop at various temperatures and flow rates for each meter of bed depth of DIAION™ CRB05 resin in normal down flow operation is shown in the graphs below.




Fig. 1 Pressure Drop of CRB05




Fig. 2 Bed Expansion of CRB05

Notice

This information are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. The application, use and processing of our products are beyond our control and therefore your own responsibility.