Product Information

Relite[™] JA830

Relite™ JA830 is a gel type strongly basic anion exchange resin. It has acrylic-DVB polymer matrix and excellent properties. A wide range of applications, especially in a field of demineralization and chemical process, is recommended.

	Relite [™] JA830
	Strong Base Anion
	Acrylic - DVB, Gel
Ту	pe I (trimethyl ammonium groups)
	Cl ⁻
-	90 min.
meq/mL	1.2 min.
%	54 - 64
%	5 max.
%	2 max.
mm	0.45 - 0.60
-	1.7 max.
ions	
°C	50 (Cl ⁻)
	40 (OH ⁻)
	0 - 14
mm	600
mm BV/h	600 10 - 25
	10 - 25
BV/h	10 - 25 NaOH
	- meq/mL % % mm -

1 BV(Bed Volume)=1 m³/m³-resin



BV

Total Rinse Requirement

Product Information Relite[™] JA830

Notice

The information contained herein is believed to be true and accurate, but all data, recommendations and suggestions are provided without guarantee, since the conditions of use are beyond our control and can affect the performance and properties of our products. The user is solely responsible for confirming that our product is suitable for the intended end use, and for compliance with all legal regulations and patents. Other than compliance with published Mitsubishi Chemical Corporation specifications agreed to pursuant to a signed writing during the warranty period, and except as required by law, MITSUBISHI CHEMICAL CORPORATION AND ITS AFFLIATES MAKE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR ANY WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If a product is found to be defective during the warranty period, user's sole remedy and our sole obligation is, at our option, replacement of the affected product or refund of the purchase price. Except as required by law, we are not liable for any damage, harm or loss resulting from our product, whether direct, indirect, consequential, incidental or special, and irrespective of legal theory asserted, including strict liability, contract, warranty, or negligence.

